



# POLYURETHANE TIMING BELTS

## IMPERIAL-SERIES

**L=T3/8"**  
(9.525mm)



**STEEL** Tension Member — standard  
**KEVLAR®** Tension Member — optional



### OPEN ENDED – M



Pulleys  
page 168

**Widths:** Standard Belt Widths (in between widths available):  
in inch: 0.375 0.5 0.75 1.0 1.5 2.0  
in mm: 9.53 12.7 19.05 25.4 38.1 50.8


**Lengths:** Any length available – Stock Rolls: 50 meters (164 feet)

#### Ordering example:


**BRECO Timing Belt** 25.4 T3/8" / 762 M or 300 L 100 M

#### Available Options (page 149):

- PAZ
- PAR
- PAZ-PAR



Belt Width										
Pitch										
Length										
Open Ended Length Code M										



### SPLICED AND WELDED ENDLESS – V




Pulleys  
page 168

**Widths:** Standard Belt Widths (in between widths available):  
in inch: 0.375 0.5 0.75 1.0 1.5 2.0  
in mm: 9.53 12.7 19.05 25.4 38.1 50.8

**Lengths:** Minimum Joined Length: 876.3 mm (34.5 inches)  
Length of timing belt can be specified in one tooth increments

#### Available Options (page 149):

- PAZ
- PAR
- PAZ-PAR




Belt Width										
Pitch										
Length										
Joined Length Code V										

# POLYURETHANE TIMING BELTS

## IMPERIAL-SERIES

**L=T3/8"**  
(9.525mm)



**STEEL** Tension Member — standard  
**KEVLAR®** Tension Member — optional



### TRULY ENDLESS - BFX



Pulleys  
page 168

**Widths:** Standard Belt Widths in mm (in between widths available):

in inch:	0.375	0.5	0.75	1.0	1.5	2.0	3.0	4.0
in mm:	9.53	12.7	19.1	25.4	38.1	50.8	76.2	101.6

Length/Pitch Code	Length in mm	Number of Teeth
124 L	314.33	33
150 L	381.00	40
187 L	476.25	50
202 L	514.35	54
210 L	533.40	56
225 L	571.50	60
240 L	609.60	64
255 L	647.70	68
270 L	685.80	72
285 L	723.90	76
300 L	762.00	80
322 L	819.15	86
345 L	876.30	92
367 L	933.45	98

Length/Pitch Code	Length in mm	Number of Teeth
390 L	990.60	104
420 L	1066.80	112
450 L	1143.00	120
480 L	1219.20	128
540 L	1371.60	144
570 L	1447.80	152
600 L	1524.00	160
630 L	1600.20	168
660 L	1676.40	176
705 L	1790.70	188
750 L	1905.00	200
1102 L	2800.35	294
2002 L	5086.35	534
3000 L	7620.00	800

Further lengths up to 14,992.35 mm (590.25 inches) available. Length of timing belt can be increased in increments of one tooth from minimum length of 1,066.8 mm (42 inches).

**Ordering example:**

**BRECOFLEX** Timing Belt 25.4 T3/8" / 762 BFX or 300 L 100 BFX

Belt Width \_\_\_\_\_

Pitch \_\_\_\_\_

Length \_\_\_\_\_

Truly Endless Length Code BFX \_\_\_\_\_

**Available Options (page 149):**

- PAZ

